

771-Favourite-PC



Under Verandah Weatherproof Batten - PC Diffuser
Durable AISI316 stainless steel mounting brackets
& tamper-proof clips made for the New Zealand
environment.

5Y
WARRANTY

IP66

IK10


i b IBV HUNGÁRIA
Lighting and Plastic Processing

FEATURES:

CODE	WATTS	DELIVERED LUMENS	LED ARRAY	DIMENSIONS (L,W,H) mm	WEIGHT Kg
771061540PC	15	2000	single	669 x 90 x 95	1.7
771123140PC	31	3800	single	1277 x 90 x 95	2.23
771125540PC	55	7800	twin	1277 x 90 x 95	2.65
771154940PC	49	6500	twin	1577 x 116 x 99	2.7
771157040PC	70	9900	twin	1577 x 116 x 99	3
771158340PC	83	12000	twin	1577 x 116 x 99	3


LIGHT QUALITY

CCT:	4000K
CRI:	>80
SCDM:	<3
Lifetime (Ta = 35°C):	>72,000 hrs L70 B50
Beam Angle:	120°
Light Emission:	Direct
Power Supply:	AC220-240V, 50/60Hz
Driver Options:	Fixed output (DALI upon request)
Driver Position:	Integrated



PHYSICAL FEATURES:

IP Rating:	IP66
IK Rating:	IK10
Body:	GRP - Glass fibre reinforced polyester
Gasket:	Non-ageing PU (polyurethane) foam
Clips & Brackets:	AISI 316 stainless steel
Diffuser:	Polycarbonate (PC) impact resistant



L: 1277mm / 1577mm

SINGLE:



H: 95 mm
W: 90 mm

TWIN:



H: 99 mm
W: 116 mm

WARRANTIES:

Warranty: Five years
Emergency available upon request please add -EM to end of code.