

PRODUCT DATASHEET LED SST D/L TRI 8 W 3000 K 4000 5000 Junction

LED SUPERSTAR DOWNLIGHT TRI-COLOUR SWITCH | LED downlight with three settable color temperatures



AREAS OF APPLICATION

- Bathrooms (IP44)
- Residential interiors
- Commercial lighting

PRODUCT BENEFITS

- Adjustable color temperature for a wide range of applications

PRODUCT FEATURES

- Three light colors selectable via slide switch
- Luminous efficacy: up to 106 lm/W
- Beam angle: 90°
- Type of protection, front side: IP44
- Lifetime: up to 30,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	8.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000/4000/5000 K	
Color rendering index Ra	≥80	
Light color (designation)	Warm White/Cool White/Daylight	
Luminous flux	750/850/820 lm	
Luminous efficacy	94.0/106/103 lm/W	

Light technical data

Beam angle	90.00 °

Dimensions & weight

Diameter	114.0 mm
Height	57.5 mm
Product weight	230.00 g
Cable length	1200 mm

Colors & materials

Body material	Polybutylene terephthalate (PBT)	
Product color	White	
Housing color	White	
Cover material	PBT (30% FIBRE-GLASS REINFORCE	

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Lifespan

Number of switching cycles	100000
Lifespan	30000 h

Additional product data

Mounting type	Recessed
Mounting location	Ceiling

Capabilities

Dimmable	Yes
Type of connection	Plug type C (EU)
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP44

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075214729	Folding carton box 1	123 mm x 123 mm x 73 mm	242.00 g	1.10 dm³
4058075214736	Shipping carton box 12	263 mm x 263 mm x 250 mm	3318.00 g	17.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.