

PRODUCT DATASHEET

LED SST GIMBLE DL 7 W 3000 K Junction box

LED SUPERSTAR GIMBLE DOWNLIGHT | Spotlights and downlights



AREAS OF APPLICATION

- Living areas (living rooms, dining rooms, bedrooms etc.)

PRODUCT FEATURES

- Lifetime: up to 30,000 h
- Adjustable swivel angle: $\pm 30^\circ$
- Beam angle: 60°
- Available with color temperature: 3,000 K, 4,000 K



TECHNICAL DATA**Electrical data**

Nominal wattage	7.00 W
Nominal voltage	220...240 V
Mains frequency	50 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	80
Luminous flux	630 lm
Luminous efficacy	90 lm/W

Light technical data

Beam angle	60 ° ¹⁾
------------	--------------------

¹⁾ ZMP_110132

Dimensions & weight

Width	85.0 mm
Height	64.5 mm
Product weight	220.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	White
Housing color	White

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

Lifespan

Lifespan	30000 h
----------	---------

Additional product data

Mounting type	Recessed
---------------	----------

Capabilities

Dimmable	Yes
Type of connection	Terminal, 3-Pole (L, N, PE)
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP40

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075214873	Folding carton box 1	110 mm x 110 mm x 80 mm	296.00 g	0.97 dm ³
4058075214880	Shipping carton box 30	350 mm x 240 mm x 425 mm	9546.00 g	35.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.