

# **PRODUCT DATASHEET**LED VALUE CLAS P FIL 4 W/2700K E27 GEN2

LED VALUE CLASSIC P FILAMENT | LED lamps, classic mini-ball shape



#### **AREAS OF APPLICATION**

- Perfect for decorative installations
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Domestic applications

#### **PRODUCT BENEFITS**

- Very low energy consumption
- Lamps with innovative LED "filament" technology
- $\,$   $\,$  No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp

#### **PRODUCT FEATURES**

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Beam angle: up to 300°
- Lifetime: up to 15,000 h



# **TECHNICAL DATA**

#### Electrical data

Rated wattage	4.00 W	
Nominal wattage	4.00 W	
Nominal voltage	220240 V	
Operating frequency	5060 Hz	
Power factor λ	> 0.50	
Claimed equiv. conventional lamp power	40 W	


#### Photometrical data

Nominal luminous flux	470 lm
Rated luminous flux	470 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	470 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Rated color temperature	2700 K

# Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & weight



Overall length	77.0 mm
Diameter	45.0 mm
Outer bulb	P45
Length	77.0 mm

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C		
Lifespan			
Nominal lamp life time	15000 h		
Rated lamp life time	15000 h		
Number of switching cycles	100000		
Lumen maintenance at end of service life	0.70		

# Additional product data

Base (standard designation)	E27		
Mercury content	0.0 mg Yes		
Mercury-free			
Show WEEE picto	Yes		
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value		

# Capabilities

Dimmable	No
----------	----


#### Certificates & standards

Energy efficiency class	A++
Energy consumption	4 kWh/1000h

# Country-specific categorizations

Order reference	LV CLP 4W/827 2
-----------------	-----------------

#### **Light Distribution**



LDC typ polar

# **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267725	Folding carton box 1	51 mm x 51 mm x 107 mm	32.00 g	0.28 dm <sup>3</sup>
4058075267732	Shipping carton box 10	266 mm x 109 mm x 121 mm	444.00 g	3.51 dm <sup>3</sup>
4058075506480	Shipping carton box 10	266 mm x 109 mm x 121 mm	446.00 g	3.51 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.