

# PRODUCT DATASHEET

## LED VALUE Superstar Downlight 9 W/3000 K/4000 K/5000 K

LED VALUE SUPERSTAR DOWNLIGHT TRI COLOR | Downlight with a variety of wattages

---

### Areas of application

- Kitchens, bathrooms, living rooms and workshops
- Residential interiors
- Corridors, entrances, foyers, stairwells, elevators



---

### Product benefits

- Cost-effective
- High efficiency and reliability
- Stylish and modern design

---

### Product features

- Three light colors selectable via slide switch
- LED downlight with integrated driver
- Type of protection: IP44
- Luminous efficacy: up to 106 lm/W



## TECHNICAL DATA

### Electrical data

Nominal wattage	9.00 W
Nominal voltage	220...240 V
Nominal current	42 mA
Power factor $\lambda$	0,90

### Photometrical data

Color temperature	3000 K/4000 K/5000 K
Luminous flux	1100 lm
Luminous efficacy	122 lm/W
Light color (designation)	Warm White / Cool White / Cool Daylight
Standard deviation of color matching	5 sdc <sub>m</sub>
Color rendering index Ra	≥80

### Light technical data

Beam angle	90 °
------------	------

### Dimensions & weight

Diameter	130.00 mm
Height	57.50 mm
Product weight	230.00 g

### Colors & materials

Body material	Aluminum
Product color	White
Housing color	White
Cover material	Polycarbonate (PC)

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Temperature range in operation	-20...+40 °C

### Additional product data

Mounting type	Recessed
Mounting location	Ceiling



## Capabilities

Dimmable	Yes
Type of connection	Plug type C (EU)
LED module replaceable	Not replaceable

## Certificates & standards

Protection class	II
Type of protection	IP44/20K

## DOWNLOAD DATA

DOWNLOAD DATA	
	Tender documents Tender Text 4058075398139
	IES file (IES) LDVAL SS DL R 9W 125 G4 TRI

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075398139	Folding box 1	123 mm x 123 mm x 73 mm	242.00 g	1.10 dm <sup>3</sup>
4058075398146	Shipping box 12	290 mm x 290 mm x 259 mm	3976.00 g	21.78 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.