

PRODUCT DATASHEET

LED VALUE Superstar Downlight 11 W/3000 K/4000 K/5000 K

LED VALUE SUPERSTAR DOWNLIGHT TRI COLOR | Downlight with a variety of wattages

Areas of application

- Kitchens, bathrooms, living rooms and workshops
- Residential interiors
- Corridors, entrances, foyers, stairwells, elevators



Product benefits

- Cost-effective
- High efficiency and reliability
- Stylish and modern design

Product features

- Three light colors selectable via slide switch
- LED downlight with integrated driver
- Type of protection: IP44
- Luminous efficacy: up to 106 lm/W



TECHNICAL DATA

Electrical data

Nominal wattage	11.00 W
Nominal voltage	220...240 V
Nominal current	51 mA
Power factor λ	0,90

Photometrical data

Color temperature	3000 K/4000 K/5000 K
Luminous flux	1300 lm
Luminous efficacy	118 lm/W
Light color (designation)	Warm White / Cool White / Cool Daylight
Standard deviation of color matching	5 sdc _m
Color rendering index Ra	≥80

Light technical data

Beam angle	90 °
------------	------

Dimensions & weight

Diameter	150.00 mm
Height	62.50 mm
Product weight	260.00 g

Colors & materials

Body material	Aluminum
Product color	White
Housing color	White
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Temperature range in operation	-20...+40 °C

Additional product data

Mounting type	Recessed
Mounting location	Ceiling



Capabilities

Dimmable	Yes
Type of connection	Plug type C (EU)
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP44/20K

DOWNLOAD DATA

DOWNLOAD DATA	
	Tender documents Tender Text 4058075398177
	IES file (IES) LDVAL SS DL R 11W 125 G4 TRI

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075398177	Folding box 1	123 mm x 123 mm x 73 mm	242.00 g	1.10 dm ³
4058075398184	Shipping box 12	330 mm x 330 mm x 250 mm	4637.00 g	27.23 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.