

EVERBUILD Stick 2 All Purpose Superglue All sizes.

DESCRIPTION AND USES

STICK 2 ALL PURPOSE SUPERGLUE is a medium viscosity high strength ethyl cyanoacrylate based adhesive. Fills gaps up to 0.1mm. For use on perfect fit surfaces where a fast set is required. Bonds non-porous surfaces such as most plastics, metals, PVCu, rubber, ceramics and much more.

APPLICATION

Ensure surfaces to be bonded are clean and dry. Apply adhesive sparingly to one surface (take care not to use too much adhesive). Assemble items by firmly pressing parts together for 30 seconds. After use, clean nozzle with a dry cloth or paper roll and firmly screw the cap back on the tube.

NOTE: Once surfaces are brought together an almost instant bond is formed, therefore great care is needed to align items as contact is made.

To de-bond use Everbuild Superglue Remover.

STORAGE

Store in cool, dry conditions between 0 and +20°C.
Storage outside these parameters will dramatically reduce shelf life.

Shelf Life

2 years from date of manufacture in original unopened tubes.

HEALTH AND SAFETY

See MSDS for details

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.