



KRATOS

EMERGENCY BULKHEAD

25W ▪ HF Sensor ▪ 4000K ▪ LED ▪ IP65

MAINTAINED / NON-MAINTAINED



AS/NZS 2293
Compliant

An IP65 and IK10 rated luminaire that comes with integral HF sensor, that is ideal for applications such as corridors, carparks, stairwells and walk ways. The Kratos is tested to comply with AS/NZS 2293 and relevant EMC standards. An IES file is available for design specification.

- Sleek circular bulkhead design
- Surface mount
- Lightweight design for quick and easy installation
- Ideal for corridors, carparks, stairwells, and walk ways
- Meets AS/NZS 2293 and relevant EMC standards
- IP65 and IK10 rated



GENERAL

Voltage	220-240VAC, 50/60Hz
Wattage	25W
PF	>0.9
LED Driver Output(V)	DC36V
LED Driver Output(mA)	600mA Max
Light Source	SMD2835 LED chips
CCT / CRI	4000K / Ra>80
Lifespan	60,000 hours
Luminous Flux	3000lm
Luminous Efficacy	120lm/W
View Angle	120°
Emergency Version	Non Maintained or Maintained
Battery	9.6V 1.5Ah LiFePO4 lithium rechargeable
Emergency Output	200lm
Emergency Duration	3 hours
Charge Time	12 hours
LED Indication	Red - charging, Green - fully charged

STRUCTURE

Housing Material	Die cast aluminium base + PC diffuser
Mounting Type	Surface Mount
Operating Temp(°C)	5°C - 45°C
IK Rating	IK10
IP Rating	IP65
Unit Dimensions	315 x 315 x 100mm



IP65

See more on our website:
www.electrical.co.nz/elmark