

# Stanilite®

## Platinum exit LED weatherproof remote



### Range

Platinum range

### Product group

Exit LED



### Features

- 5 year warranty
- Used in combination with remote power supply; exit mounted inside the freezer or coolroom and remote power supply mounted outside up to 10m away from the exit
- LED technology 100,000 hours plus lamp life
- LED light source for reduced operation and maintenance costs
- IP65 weatherproof enclosure
- UV stabilised vandal resistant (IK08) polycarbonate cover
- Increased safety and no shock hazard by isolating the AC primary circuits from the unit
- Ideal for freezer or coolroom applications up to -30°C
- Surface mount
- Removable gear tray for easy installation and maintenance
- Remote power supply available in standard, Nexus® LX and Nexus RF configurations. Refer to separate technical data sheets; PSLED1W6P, PSNXSLED1W6P, PSNRFLED1W6P, WPPSLED1W6P, WPPSNXSLED1W6P, WPPSNRFLED1W6P
- Not suitable for installations where exposure to direct sunlight may occur

Catalogue no.	Description
<b>Standard products</b>	
PWEXLEDREM-1P	Platinum exit LED weatherproof remote picto - body only
PWEXLEDREM-2P	Platinum exit LED weatherproof remote <picto - body only
PWEXLEDREM-3P	Platinum exit LED weatherproof remote picto> - body only
<b>Accessories</b>	
WPEXWGWM	Wire guard



Dimensions			
	Length	Width	Height
	380mm	130mm	190mm
Weight			
	Model	Weight	
	Standard	1.8kg	
Construction			
	Part	Construction	
	Enclosure	Polycarbonate	
	Gear tray	White powder coated zinc steel	

Light source			
	Model	Light source	
	Standard	Multiple LED 1.6W	
Power consumption			
	Model	Power consumption	
	Standard/Nexus LX/Nexus RF	See separate technical data sheets; PSLED1W6P, PSNXSLED1W6P, PSNRFLED1W6P, WPPSLED1W6P, WPPSNXSLED1W6P, WPPSNRFLED1W6P	
Photometrics			
	Model	Class	Classification
	Standard	C0	D1.25
		C90	C1.25
Note: Preliminary results			

Note:

- Designed to comply with AS2293 and meet relevant Australian EMC standards