

## Presence detector

# IR Quattro HD

EAN 4007841002756



## Functional description

HD isn't just restricted to televisions but from now on also used in presence detectors. Because Presence Control PRO IR Quattro HD provides extremely high-definition detection. 4,800 switching zones and a square detection footprint with a presence zone covering a true 64 m<sup>2</sup> leave no margin whatsoever for inadvertent triggering and blind spots. Unique: The presence zone can be mechanically scaled without the slightest loss of quality. This means IR Quattro HD applications in medium to large-size offices, conference and meeting rooms, class rooms and lecture theatres as well as sports halls and warehouses can be planned and configured with absolute precision. Something others can only dream of.

## Technical specifications

<b>Type</b>	Presence detector
<b>Dimensions (L x W x H)</b>	120 x 120 x 65 mm
<b>Mains power supply</b>	230 V, 50 / 60 Hz
<b>Sensor Technology</b>	passive infrared
<b>Application, place</b>	Indoors
<b>Installation site</b>	ceiling
<b>Type of installation</b>	Concealed wiring
<b>Switching zones</b>	4800 Schaltzonen
<b>Electronic scalability</b>	No
<b>Mechanical scalability</b>	Yes
<b>Mounting height</b>	2,50 – 10,00 m
<b>Optimum mounting height</b>	2,8 m
<b>Detection angle</b>	360 °
<b>Capability of masking out individual segments</b>	No
<b>Reach, radial</b>	8 x 8 m (64 m <sup>2</sup> )
<b>Reach, tangential</b>	20 x 20 m (400 m <sup>2</sup> )
<b>Reach, presence</b>	8 x 8 m (64 m <sup>2</sup> )
<b>Twilight setting TEACH</b>	Yes
<b>Twilight setting</b>	10 – 1000 lx
<b>Time setting</b>	30 s – 30 min
<b>Control output, DALI</b>	Broadcast 2x12 electronic ballasts
<b>Constant-lighting control</b>	Yes
<b>Basic light level function</b>	No
<b>Basic light level function in per cent</b>	10 – 50 %
<b>Basic light level function time</b>	Permanently ON, 1-255 min, all night
<b>Functions</b>	Normal / test mode, Semi-/fully automatic, Pushbutton / switch mode, Manual ON / ON-OFF, Constant-lighting control ON-OFF
<b>Settings via</b>	ETS software, Remote control, Bus
<b>With remote control</b>	No
<b>Sensor</b>	Yes
<b>Type of interconnection</b>	Master/slave
<b>IP rating</b>	IP20
<b>Material</b>	Plastic

<https://www.steinel-professional.de/>

Presence detector

## IR Quattro HD

EAN 4007841002756

<b>Ambient temperature</b>	-25 – 55 °C
----------------------------	-------------

<b>Colour</b>	white
---------------	-------

<b>Colour, RAL</b>	9010
--------------------	------

<b>Manufacturer's Warranty</b>	5 years
--------------------------------	---------

<b>Version</b>	DALI
----------------	------

Presence detector

## IR Quattro HD

EAN 4007841002756

### Sensorenerfassungsbereich 1

