
L 600 CAM

EAN 4007841 052997



























781 lm, 54 lm/W

max. radius 10 m

Function description

Smart. Save. Intelligent. L 600 CAM is a sensor-switched camera and intercom system in one product. With integrated micro SD memory card and camera to get razor-sharp images onto the smartphone or tablet (Wi-Fi and app-based). Enclosure in aluminium and high-quality opal glass. 180° infrared motion sensor with 10 m reach. Warm-white light: 3000 K and 781 Im at 14,3 W.

Technical specifications

131 x 78 x 305 mm
220 – 240 V / 50 – 60 Hz
2,00 m
passive infrared
14,3 W
No
781 lm
54 lm/W
3000 K
80-89
Yes, STEINEL LED system
LED cannot be replaced
50000 h
without
Passive Thermo Control
Yes
180 °
90 °
No

Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	passive infrared: Passiv Infrarot: $r = 2 \text{ m}$ (Passiv Infrarot: 6 m^2)
Reach, tangential	passive infrared: Passiv Infrarot: r = 10 m (Passiv Infrarot: 157 m²)
Photo-cell controller	Yes
Twilight setting	10 – 10000 lx
Time setting	60 s – 15 Min.
Basic light level function	Yes
Soft light start	Yes
IP rating	IP44
Protection class	I
Ambient temperature	-10 – 40 °C
Housing material	Aluminium
Cover material	Glass opal
Manufacturer's Warranty	3 years
Settings via	Smartphone
With remote control	Yes
PU1, EAN	4007841052997


Sensor-switched outdoor light

L 600 CAM

EAN 4007841 052997



Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,00 m Orange: radial Schwarz: tangential

Dimension Drawing

