


Presence detector

IR Quattro MICRO COM1

EAN 4007841053789



Functional description

Small, precise and effective. Required by planners and architects, made by STEINEL. The IR Quattro MICRO fulfills many wishes. Its small size and the low profile design make it perfect for applications where disturbing installations on the ceiling are to be avoided. The size of the micro-precision lens is just 15 x 15 mm. And its performance is nevertheless stunning. The 360° infrared presence detector detects 36 m². And the IP65 classification lets you install it in rooms that are subject to moisture. The IR Quattro MICRO – our smallest unit with high potential.

Technical data

| | |
|--|--------------------------|
| Type | Presence detector |
| Dimensions (Ø x H) | 43 x 70 mm |
| Mains power supply | 220 – 240 V , 50 / 60 Hz |
| Sensor type | Passive infrared |
| Switching zones | 168 Schaltzonen |
| Mechanical scalability | No |
| Electronic scalability | No |
| Mounting height | 2,00 – 5,00 m |
| Optimum mounting height | 2,80 m |
| Switching output 1, resistive | 1000 W |
| Switching output 1, number of LEDs / fluorescent lamps | 8 stk. |
| Motion detection | 6 x 6 m |
| Presence detection | 4 x 4 m |
| Detection angle | 360 ° |
| Light-level setting TEACH | Yes |
| Twilight setting | 2 – 1000 lx |
| Time setting | 30 s – 60 min |
| Type of installation | Installation |

Presence detector

IR Quattro MICRO COM1

EAN 4007841053789

Technical data

| | |
|----------------------------------|---------------|
| IP rating | IP65 |
| Material | Plastic |
| Ambient temperature | -25 – 55 °C |
| With remote control | Yes |
| Constant-lighting control | No |
| Colour | White |
| Manufacturers warranty | 5 years |
| PU1, EAN | 4007841053789 |